

STSM T5



FELHASZNÁLÁSI TERÜLET

AZ STSM T5 LÁMPACSALÁD ÁRUHÁZAK, ELADÓTEREK, FOLYOSÓK ÁLTALÁNOS MEGVILÁGÍTÁSÁRA AJÁNLOTT.

ANYAG

LÁMPATEST: EPOXY POLÉSZTER ALAPÚ FESTÉSEL BEVONT ACÉLLEMEZ RAL 9003 SZÍNBEN
FÉNYTERELŐ: LÁMPATESTHÁZZAL AZONOS SZÍNRE FESTETT ACÉLLEMEZ VAGY TÜKRÖSÍTETT ALUMÍNIUM LE-
MEZ

RÖGZÍTÉS

A LÁMPATESTEK MENNYEZETRE VAGY FÜGGESZTVE SZERELHETŐK

GYÁRTÁS

A LÁMPATESTEK RENDELHETŐK EVG, DIMM EVG, VÉSZVILÁGÍTÓ EGYSÉGGEL SZERELT KIVITELBEN.

IGÉNY ESETÉN A KÖNNYEBB SZERELÉS ÉRDEKÉBEN GYORSCSATLAKOZÓS KIVITELBEN IS RENDELHETŐK.

FIELD OF APPLICATION

THE STSM T5 RANGE OF LUMINAIRES IS SUGGESTED FOR GENERAL ILLUMINATION OF DEPARTMENT STORES, SALES AREAS, CORRIDORS.

BASE MATERIAL

BODY OF THE LUMINAIRE: EPOXY POLYESTER BASED PAINTED STEEL SHEET IN RAL 9003 COLOUR.
REFLECTOR: PAINTED STEEL SHEET IN THE SAME COLOUR AS THE LUMINAIRE OR MIRROR POLISHED ALUMINIUM SHEET.

FIXING

THE LUMINAIRES CAN BE MOUNTED ONTO THE CEILING OR SUSPENDED.

MANUFACTURING

THE LUMINAIRES ARE AVAILABLE IN EVG, DIMM EVG, INVERTER VERSION.

UPON CUSTOMER'S REQUEST THE LUMINAIRES CAN BE ORDERED WITH QUICK CONNECTOR SET FOR EASIER INSTALLATION.





230V
50Hz



IP20



1F

3F



| Rendelési kód | Típus | Foglalat | Teljesítmény | A (mm) | B (mm) | C (mm) | D (mm) | E (mm) | Térfogat (m ³) | Csom. egy-ség | Súly (kg) | Energiaosztály |
|---------------|----------|----------|--------------|--------|--------|--------|--------|--------|----------------------------|---------------|-----------|----------------|
| 60 272 114 | STSM-114 | G5 | 1X14W | 585 | 135 | 102 | 330 | 80 | 0.010 | 4 | 1.3 | A |
| 60 272 124 | STSM-124 | G5 | 1X24W | 585 | 135 | 102 | 330 | 80 | 0.010 | 4 | 1.3 | A |
| 60 272 128 | STSM-128 | G5 | 1X28W | 1185 | 135 | 102 | 930 | 80 | 0.019 | 4 | 2.4 | A |
| 60 272 154 | STSM-154 | G5 | 1X54W | 1185 | 135 | 102 | 930 | 80 | 0.019 | 4 | 2.4 | A |
| 60 272135 | STSM-135 | G5 | 1X35W | 1485 | 135 | 102 | 1230 | 80 | 0.026 | 4 | 2.9 | A |
| 60 272 149 | STSM-149 | G5 | 1X49W | 1485 | 135 | 102 | 1230 | 80 | 0.026 | 4 | 2.9 | A |
| 60 272 180 | STSM-180 | G5 | 1X80W | 1485 | 135 | 102 | 1230 | 80 | 0.026 | 4 | 2.9 | A |
| 60 272 214 | STSM-214 | G5 | 2X14W | 585 | 135 | 102 | 330 | 80 | 0.010 | 4 | 1.3 | A |
| 60 272 224 | STSM-224 | G5 | 2X24W | 585 | 135 | 102 | 330 | 80 | 0.010 | 4 | 1.3 | A |
| 60 272 228 | STSM-228 | G5 | 2X28W | 1185 | 135 | 102 | 930 | 80 | 0.019 | 4 | 2.4 | A |
| 60 272 254 | STSM-254 | G5 | 2X54W | 1185 | 135 | 102 | 930 | 80 | 0.019 | 4 | 2.4 | A |
| 60 272 235 | STSM-235 | G5 | 2X35W | 1485 | 135 | 102 | 1230 | 80 | 0.026 | 4 | 2.9 | A |
| 60 272 249 | STSM-249 | G5 | 2X49W | 1485 | 135 | 102 | 1230 | 80 | 0.026 | 4 | 2.9 | A |
| 60 272 280 | STSM-280 | G5 | 2X80W | 1485 | 135 | 102 | 1230 | 80 | 0.026 | 4 | 2.9 | A |

